

ROW Precision Balance

General Specifications

- | | |
|-------------------|--|
| • Display | 22mm digit LCD display, with white LED backlight |
| • Capacities | 3kg, 7kg, 15kg |
| • Pan size | Ø232mm |
| • Keyboard | 6 keys (Mechanical switch) |
| • Housing | ABS plastic indicator |
| • Max. Divisions | 30,000d; 70,000d; 150,000d |
| • ADC | Sigma delta |
| • ADC update | ≤ 1/10 second |
| • Operating Temp. | 0°C ~ +40°C |
| • Power | AC adapter (12V/500mA), Ni-MH battery (1.2V/2000mAh x 6) |
| • Gross weight | 3.8kg |



- Stainless steel platform
- An economical general purpose instrument
- Applications: 1. Net/gross shift 2. Weighing unit conversion 3. Check weighing
- Battery provides up to 40 hours of continuous use (without backlight)
- Standard RS-232 to connect to computer
- Optional initial-verification



ROW Precision Balance

Model Name	Capacity	Readability	Division	Approx. weight	Approval
ROW-3K	3kg	0.1g	30,000d	3.8kg	CE
ROW-7K	7kg	0.1g	70,000d	3.8kg	CE
ROW-15K	15kg	0.1g	150,000d	3.8kg	CE

Options



Dimensions(mm)

